

## KEYNOTES:

- (03-1) 2" x 5-1/2" BOLT-IN FRAME: 12 GA. ST EEL, PRIMED FINISH; UL LEVEL 8
- 03-3 4-3/4" x 4" ANCHOR PLATE: 12 GA. S TEEL, PRIMED FINISH
- 1-1/4" x 1-1/4" REMOVABLE STOP: 12 GA. STEEL, PRIMED FINISH

106 GUADALUPE DRIVE CIBOLO TX, 78108 PHONE # (210) 225-0982

WEBSITE: www.nabulletproof.com

ALL RIGHTS RESERVED

FAX # (210) 225-0984

NABP P.O BOX 628

NORTH AMERICAN

UL LEVEL 8 GLAZING

(03-14)

03-4

(03-17)


- GLAZING TAPE (SUPPLIED) AND SEALANT (BY OTHERS)
- MOUNTING SCREW
- TYPICAL WALL CONSTRUCTION (BY OTHERS)
- ANCHOR, AS REQUIRED (BY OTHERS)

01-4

01-3

01-5) BULLET-RESISTANT ARMOR, UL LEVEL 8





(03-4)

SECURE SIDE

) ELEVATION/PLAN

01-4

(03-14)

51/2"

THREAT SIDE

B JAMB DETAIL 1

01-3

 $\langle 03-3 \rangle$ 

(03-1)

01-5

01-4

03-1

C) SILL DETAIL

01-5

COMMENTS:

WITHOUT WRITTEN PERMISSION OF

THAN THE SPECIFIED PROJECT

NORTH AMERICAN BULLET PROOF

AND SHALL NOT BE REPRODUCED IN WHOLE OR PART. IT SHALL NOT BE USED FOR CONSTRUCTION OF OTHER

NORTH AMERICAN BULLET PROOF

THIS DRAWING IS THE PROPERTY OF

## **JAMB DETAIL 2** THREAT SIDE

EXVW8-P-BF